### **SCRAM** authentication

Michael Paquier – VMware 2017/12/06, PGConf Asia 2017

### Authentication methods

- Password
  - Plain text
  - MD5
  - SCRAM-SHA-256
  - RADIUS, Idap, pam, BSD...
- SSL certificates
- Kerberos, SSPI (Windows)
- peer
- https://www.postgresql.org/docs/current/static/authmethods.html#AUTH-BSD

### Plain text

Password sent in clear text

Server: Please send your password

Client: "hoge"

Server: OK, good to go

- Can be used with SSL!
  - sslmode = verify-full
  - sslmode = prefer, the default, is an abomination
- Weak to password sniffing, across network.

#### MD5

Password hash sent:

Server: Here is a salt (4 random bytes), please compute

md5(md5(password || username), salt)

Client: "ad22f1df5331cfa7603c67a2092c6159"

Server: OK, good to go

- Can still be used with SSL!
- Issues
  - User rename
  - MD5 is said to be \*bad\* (see community lists).

### Attacking MD5 hash

- Guess attack
  - Hash calculation is fast (Millions per second)
- Replay attack
  - Salt is 4 bytes
  - 4-billion possibilities
- Pass-the-hash
  - Connection possible just by knowing the stored hash.
  - Old backups lying around?

### Deprecated features in v10

#### Removal

- password\_encryption = off/plain is removed
- Plain text entries in pg\_authid
- createuser --unencrypted

#### libpq

- PQencryptPassword() is deprecated.
- Use PQencryptPasswordConn().
- psql's \password uses it and sets password hash to password\_encryption.

### **About SCRAM**

- Salted Challenge Response Authentication
   Mechanism
- Implementation of SCRAM-SHA-256
- RFCs
  - 5802: https://tools.ietf.org/html/rfc5802
  - 7677: https://tools.ietf.org/html/rfc7677
- New in PostgreSQL 10
- RFC compliant
  - Note that username is sent empty

# SCRAM protocol

Challenge-based exchange

```
Client: Here is a random nonce (18 bytes) r=ReZelvordKIQsS5/uybHrLKa
```

Server: Here is my random nonce, salt and iteration count r=ReZeIvordKIQsS5/uybHrLKaJ4YZ83N/PitA0fx0eEmj1Gro, s=aqgRYGF+L5LUrYpej98rgA==, i=4096

Client: Proof that I know the password. p=O/BAMj7s/fbE5UvMKfhXRmObj/s2hlD23sMqUIIIsxk=

Server: Proof that I also know the password. v=JyGOhjHVCnLjCbJuC/XTICPPQFQ2fGk8+sCbSq2g+5I=

# SCRAM security

- Replay attacks => longer nonces
- Hashed stored in pg\_authid cannot be used directly.
- Dictionary attacks
  - Iteration count can be used as parameter
  - Computation of connection proof is costly (cost in connection startup)

#### SCRAM-SHA-256

- SCRAM originally uses SHA-1.
- SHA-256,384 and 512 functions available in src/common/sha2\*.c.
- Only uses SHA-256 as hash function.

### Verifiers

- Still one verifier per role.
- No dependency on role name (no removal on rename).
- Complicates upgrade scenarios.
- Controlled by password\_encryption
  - Default to 'md5'

```
=# SET password_encryption TO 'md5';
SET
=# CREATE ROLE role_md5 PASSWORD 'hoge';
CREATE ROLE
=# SET password_encryption TO 'scram-sha-256';
SET
=# CREATE ROLE role_scram PASSWORD 'hoge';
CREATE ROLE
```

### **Format**

- Usable with LDAP
- SCRAM-SHA-256\$<iteration count>:
   <salt>\$<StoredKey>:<ServerKey>

# pg\_hba.conf

```
# Local connections for Unix domain sockets
# TYPE DATABASE USER ADDRESS METHOD
local all all trust

# md5 authentication with SSL from dev machines
hostssl all all dev.example.com md5

# SCRAM for the rest, still with SSL
hostssl all all scram-sha-256
```

https://www.postgresql.org/docs/current/static/auth-pg-hba-conf.html

# Support server-client

With password, md5 and scram-sha-256...

	hba configuration		
Verifier type	password	md5	scram-sha-256
MD5	O [1]	Ο	X
SCRAM-SHA-256	O [1]	O [2]	О

[1]: Plain text is used, hash generated server-side.

[2]: SCRAM is used.

#### Extra work with v10

- Middleware support
  - pgbouncer (patch available on github)
  - pgpool
- Drivers: https://wiki.postgresql.org/wiki/List of drivers
  - ODBC, stuff using libpq => OK
  - JDBC supports protocol

# Future improvements

- LDAP extension, storage of SCRAM verifier
- Channel binding
- Iteration count configurable
- Not possible to enforce scram in libpq, rogue servers can force downgrades:(

### Upgrade to SCRAM

- Update pg\_hba.conf (not mandatory)
  - Password, md5 to scram-sha-256
- Client updates, only libpq >= v10 supports
   SCRAM
- password\_encryption = 'scram-sha-256' in postgresql.conf.
- Change user passwords.
- Note: still only one password per role :(

# SCRAM and encryption

- SCRAM = authentication, not encryption.
- Please still use with sslmode=verify-full in v10.
- With channel binding, setup gets easier.

### **About SASL**

- Simple Authentication and Security Layer
- RFC 4422: https://tools.ietf.org/html/rfc4422
- "Framework for authentication and data security in Internet protocols. It decouples authentication mechanisms from application protocols, in theory allowing any authentication mechanism supported by SASL to be used in any application protocol that uses SASL."
- SCRAM is a SASL mechanism.
- Client drivers could use generic SASL and SCRAM implementation as Postgres is RFC-compliant.
- DIGEST-MD5 or others could be added.

# Channel binding

- MITM prevention, by "binding" FE/BE
- RFC 5929: https://tools.ietf.org/html/rfc5929
- Ensure that the point where a connection is done is still the same.
- Channel types:
  - unique: a specific connection is sure to be used.
  - endpoint: the endpoints are the same.

# Channel binding for Postgres

- Two channel types
  - tls-unique, ensure that using a hash of the TLS end message.
  - tls-server-end-point, using a hash of server certificate (useful for JDBC).
- OpenSSL has support (fancy research).
- Macos, gnuTLS (?) and Windows not directly.
- Connection parameters
  - Channel binding name.
  - Allow client to choose with or without.
- Patch for v11 in review.

Questions?